

NEW

RAFT



S3S EN ISO 20345 : 2022 S3S SR FO CI HI

STANDARD VERSION
2022

PRODUCT CHARACTERISTICS



Non-magnetic

PARADE TECHNOLOGY EXTRAS



Supports the arch of the foot



New DRS version



Extra-flexible sole



LIGHT,
COMFORTABLE
TRAINER

■ 9834 BLACK | 35 ▶ 48

COMPOSITION

Upper	PU Microfibre
Lining	3D Mesh
Toe	Composite
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Non-metallic
Sole	Dual-density polyurethane
Weight size 42*	550 g *Weight per shoe

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic/Nals flooring (soap solution)	0,36	0,36	0,31	0,35
SR Ceramic + glycerine flooring	0,22	0,24	0,19	0,28

SAFETY TABLE



Toe protection
(Safety toe cap)



Slip resistance
Ceramic floors + detergent



E Energy-absorbing heel



A Antistatic



PS Puncture-resistance
Non-metallic insert
Small spike test (3.0 mm)



SR Slip-resistance
(ceramic flooring + oil)



FO Hydrocarbon resistance



CI Sole insulation (cold)



HI Sole insulation (heat)



WPA Water-repellent upper