

PARAFA



S3S EN ISO 20345 : 2022 S3S SR FO LG CI HI



**STANDARD VERSION
2022**

PRODUCT CHARACTERISTICS



Non-magnetic



Offset
heel



Sole
insulation
(cold)



Sole
insulation
(heat)

PARADE TECHNOLOGY EXTRAS



Supports the
arch of the foot



Shock wave
dissipation



8824 BLACK AND ORANGE | 36 ► 48

COMPOSITION

Upper	Microfibre
Lining	3D mesh
Toe	Composite
Insole	Mesh over PU foam. Removable
Anti-puncture sole	Fabric SP
Sole	Dual-density polyurethane
Weight size 42*	518 g *Weight per shoe

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic/Nals flooring (soap solution)	0,36	0,54	0,31	0,40
SR Ceramic + glycerine flooring	0,22	0,28	0,19	0,24

SAFETY TABLE



Toe protection
(Safety toe cap)



Slip-resistance
Ceramic flooring + detergent



Energy-absorbing heel



Antistatic



Puncture-resistance
Non-metallic insert
Small spike test (3.0 mm)



Slip-resistance
(ceramic flooring + oil)



Hydrocarbon resistance



Sole insulation (cold)



Sole insulation (heat)



Water-repellent upper