

# PARUSA



**S3S** EN ISO 20345 : 2022 S3S SR FO LG CI HI



STANDARD VERSION  
2022



8824 BLACK AND ORANGE | 36 ▶ 48

## COMPOSITION

<b>Upper</b>	Microfibre
<b>Lining</b>	3D mesh
<b>Toe</b>	Composite
<b>Insole</b>	Mesh over PU foam. Removable
<b>Anti-puncture sole</b>	Fabric SP
<b>Sole</b>	Dual-density polyurethane
<b>Weight size 42*</b>	534 g *Weight per shoe

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic/Nals flooring (soap solution)	0,36	<b>0,54</b>	0,31	<b>0,40</b>
SR Ceramic + glycerine flooring	0,22	<b>0,28</b>	0,19	<b>0,24</b>

## PRODUCT CHARACTERISTICS



Non-magnetic



Offset heel



Sole insulation (cold)



Sole insulation (heat)

## PARADE TECHNOLOGY EXTRAS



Supports the arch of the foot



Shock wave dissipation

## SAFETY TABLE



Toe protection (Safety toe cap)



Slip-resistance Ceramic flooring + detergent

E

Energy-absorbing heel

A

Antistatic



Puncture-resistance Non-metallic insert Small spike test (3.0 mm)



Slip-resistance (ceramic flooring + oil)



Hydrocarbon resistance



Sole insulation (cold)



Sole insulation (heat)



Water-repellent upper



Grip system (offset heel)