

NEW

ROWING



S3 EN ISO 20345: 2022 S3 SR FO CI HI

STANDARD VERSION | 2022

PRODUCT CHARACTERISTICS



Insulated sole (cold)



Insulated sole (heat)



ESD

PARADE

TECHNOLOGIES



Supports the arch of the foot



New DRS version



Extra-flexible sole



8844 BLACK | 35 ▶ 48

COMPOSITION

Upper	Microfibre + PU
Front reinforcement	Injected PU
Lining	3D mesh
Toe cap	Steel
Insole	Mesh over PU foam. Removable.
Anti-puncture sole	Stainless steel
Sole	Two-density polyurethane
Weight size 42*	600 g * Weight per shoe

**	Coefficient obtained size 42	Front		Heel	
		Standard	Parade	Standard	Parade
	Ceramic floor / Nals (soap solution)	0,36	0,36	0,31	0,34
	SR Ceramic floor + Glycerine	0,22	0,23	0,19	0,26

SAFETY TABLE

	Toe protection (safety toe cap)		Sole insulation (cold)
	Slip resistance ** Ceramic floors + detergent		Sole insulation (heat)
	E Energy-absorbing heel		Electrostatic dissipation
	A Anti-static		
	P Puncture-resistance Metallic insert Wide point test (4.5 mm)		
	SR Slip resistance ** (ceramic floor + oil)		
	WPA Water-repellent upper		
	FO Hydrocarbon-resistant		