

GRINDA



STPS EN ISO 20345:2022+A1:2024 SR FO CI HI SC
ASTM F2413-24 I C PR SD100

2022 STANDARD VERSION

PRODUCT CHARACTERISTICS



Sole insulation (cold)



Sole insulation (heat)



Abrasion-resistant stone guard



Resistance to hydrocarbons



ESD



7846 ORANGE | 37 ▶ 48



7842 BLUE | 37 ▶ 48



7840 GREY | 37 ▶ 48

COMPOSITION

Upper	Mesh + Microfibre
Front reinforcement	TPU
Lining	Mesh
Toe	Polycarbonate
Insole	Mesh over PU foam
Anti-puncture sole	Fabric
Sole	Two-density polyurethane
Weight size 42*	535 g *Weight per shoe

**

Size coefficient 42	front		heel	
	Standard	Parade	Standard	Parade
Ceramic floor / Nals (soap solution)	0,36	0,38	0,31	0,41
SR Ceramic floor + glycerine	0,22	0,26	0,19	0,29

SAFETY TABLE



Toe protection (Safety toe cap)



Slip-resistance **
Ceramic flooring + detergent



Energy-absorbing heel



Anti-static



Puncture-resistance
Non-metallic insert
Small spike test (3.0 mm)



Slip-resistance **
(ceramic flooring + oil)



Hydrocarbon resistance



Abrasion-resistant stone guard



Sole insulation (cold)



Sole insulation (heat)



Electrostatic dissipation